# **CHORUS - DOMESTIC RANGE**

## WHITE MODULAR DEVICES

#### **TELEPHONE SOCKETS**

GW10403

			_
NITERNATIONIAL	CTANDADD TEL	EPHONE CONNECTOR	-
MIFRMAIMMAL	<b>NIAMIDARD IFI</b>	FRAUMECOMMECTOR	5

Code	Description	Туре	Connection	No. Chorus modules	Pack Carton
GW 10 401	RJ11		Toolless	1	1/24
GW 10 402	RJ11	In out	Impact tool	1	1/24
GW 10 403	RJ11	Double	Impact tool	1	1/24
GW 10 404	RJ12		Toolless	1	1/24

CHARACTERISTICS: insulator punching connection. GW10402 connector with double terminal board (input and output) to facilitate the shunt of a second line. APPLICATIONS: RJ11: telephone, telefax, modem. RJ12: intercommunicating internal systems.

10	A	DOUBLE CO	DOUBLE CONNECTOR WITH ADSL FILTER					
W1041		Code	Description	No. Chorus modules	Pack Carton			
G	TAXABLE PARTY.	GW 10 410	ADSL filter with RJ11 dual Soutlet for telephone	2	1/24			
			BUS-type rear terminal for connecting up to 4 cables. Built-in ADSL filter. be used for the simultaneous connection of telephone devices and modem/PC.					



FRENCH STANDARD TELEPHONE CONNECTOR				
Code	Description	Connection	No. Chorus	Pack
			modules	Carton
GW 10 405	8 contacts	Screw-on terminals	1	1/24



<b>ISRAELI ST</b>	ANDARD TELEPHON	IE CONNECTOR		
Code	Description	Connection	No. Chorus modules	Pack Carton
GW 10 406	6 contacts	Screw-on terminals	1	1/24

#### **D**ATA SOCKETS

t21	-
GW10421	-
9	

<b>RJ45 CONN</b>	IECTORS						
Code	Description	Number	Category	Cables	Connection	No. Chorus	Pack
		pairs	of use			modules	Carton
GW 10 421	RJ45	4	5e	UTP	Toolless	1	1/24
GW 10 422	RJ45	4	5e	FTP	Toolless	1	1/24
GW 10 423	RJ45	4	6	UTP	Toolless	1	1/24
GW 10 424	RJ45	4	6	FTP	Toolless	1	1/24

APPLICATIONS: LANs up to 100MHz (e.g. Ethernet, Token Ring networks) for cat. 5e LANs up to 250MHz (e.g. Videoconference systems, CCTV) for cat. 6 NOTES: circuit identification label included.

0431	in state of
V10	
GW1	

NTAINER PREARRANGED FOR HO	OUSING RJ45 DATA CONNECTORS	
For connector	No. Chorus	Pack
type	modules	Carton
Keyston Jack	1	1/48
	For connector type	type modules

NOTES: According to the technological developments and to the dimensional variations introduced by the manufacturers of connectors, it is advisable to advance a practical test in order to check the full compatibility between the connector and the Gewiss empty enclosure.



GW10443

<b>BUSHES IN</b>	OPTICAL FIBRE			
Code	Description	Туре	No. Chorus modules	Pack Carton
GW 10 425	O.F. ST Bush	Bush duplex 50/125u	1	1/24
GW 10 426	O.F. SC Bush	Bush duplex 50/125u	1	1/24
GW 10 427	O.F. MT-RJ Bush	Bush duplex 50/125u	1	1/24

CHARACTERISTICS: Precise jointing and signal transmission without any attenuation. GW10425 ST bayonet connection; GW10427 MT-RJ coupling connection; GW10426 SC coupling connection.

## **CONNECTORS FOR CONVENTIONAL NETWORKS**

CONNECTO	ORS FOR CONVENTIONAL NETWORKS			
Code	Description	Connection	No. Chorus modules	Pack Carton
GW 10 441	SUB-D 9 contacts	Weld-in	2	1/12
GW 10 442	SUB-D 15 contacts	Weld-in	2	1/12
GW 10 443	SUB-D 25 contacts	Weld-in	3	1/16
GW 10 445	BNC 50/75/93 cavo RG 58/59/62	Weld-in	1	1/12

CHARACTERISTICS: GW10445 BNC 50 Ohm (Ethernet networks); BNC 75/93 Ohm (video control systems, terminal connections).

APPLICATIONS: SUB-D connectors suitable for point-point connections for interfacing computers, peripheral devices, modems, etc... NOTES: circuit identification label included.

@=June 2012

# CHORUS - DOMESTIC RANGE

BLACK MODULAR DEVICES

### **TELEPHONE SOCKETS**

1	GW12403	

INTERNATIONAL	STANDARD 1	<b>FELEPHONE</b>	CONNECTORS

Code	Description	Туре	Connection	No. Chorus	Pack
				modules	Carton
GW 12 401	RJ11		Toolless	1	1/24
GW 12 402	RJ11	In out	Impact tool	1	1/24
GW 12 403	RJ11	Double	Impact tool	1	1/24
GW 12 404	RJ12		Toolless	1	1/24

CHARACTERISTICS: insulator punching connection. GW12402 connector with double terminal board (input and output) to facilitate the cutout of a second line. APPLICATIONS: RJ11: telephone, telefax, modem. RJ12: intercommunicating internal systems.

12410	DOUBLE CO	DOUBLE CONNECTOR WITH ADSL FILTER						
	Code	Description	No. Chorus	Pack				
			modules	Carton				
	GW 12 410	ADSL filter with RJ11 dual Soutlet for telephone	2	1/24				
GM134		BUS-type rear terminal for connecting up to 4 cables. Built-in ADSL filter be used for the simultaneous connection of telephone devices and modem/PC.						

ю	
GW12405	
LW1	
0	

FRENCH STANDARD TELEPHONE CONNECTOR						
Code	Description	Connection	No. Chorus modules	Pack Carton		
GW 12 405	8 contacts	Screw-on terminals	1	1/24		



ISRAELI STANDARD TELEPHONE CONNECTOR						
Code	Description	Connection	No. Chorus modules	Pack Carton		
GW 12 406	6 contacts	Screw-on terminals	1	1/24		

#### **D**ATA SOCKETS

<del></del>	Contract of the local division of the local
2	
2421	
2	
5	
GW1	
6	a subscription of the
0	
	and the second se

RJ45 CONNECTORS							
Code	Description	Number pairs	Category of use	Cables	Connection	No. Chorus modules	Pack Carton
GW 12 421	RJ45	4	5e	UTP	Toolless	1	1/24
GW 12 422	RJ45	4	5e	FTP	Toolless	1	1/24
GW 12 423	RJ45	4	6	UTP	Toolless	1	1/24
GW 12 424	RJ45	4	6	FTP	Toolless	1	1/24

APPLICATIONS: LANs up to 100MHz (e.g. Ethernet, Token Ring networks) for cat. 5e LANs up to 250MHz (e.g. Videoconference systems, CCTV) for cat. 6 NOTES: circuit identification label included.

EMPTY CO	EMPTY CONTAINERS FOR HOUSING RJ45 DATA CONNECTORS						
Code	For connector	No. Chorus	Pack				
	type	modules	Carton				
GW 12 431	Keyston Jack	1	1/48				

NOTES: According to the technological developments and to the dimensional variations introduced by the manufacturers of connectors, it is advisable to advance a practical test in order to check the full compatibility between the connector and the Gewiss empty enclosure.

GW12425

GW1 2443

GW12431

BUSHES IN OPTICAL FIBRE						
Code	Description	Туре	No. Chorus modules	Pack Carton		
GW 12 425	O.F. ST Bush	Bush duplex 50/125u	1	1/24		
GW 12 426	O.F. SC Bush	Bush duplex 50/125u	1	1/24		
GW 12 427	O.F. MT-RJ Bush	Bush duplex 50/125u	1	1/24		

CHARACTERISTICS: Precise jointing and signal transmission without any attenuation. GW12425 ST bayonet connection; GW12426 SC coupling connection; GW12427 MT-RJ coupling connection.

## **CONNECTORS FOR CONVENTIONAL NETWORKS**

CONNECTORS FOR CONVENTIONAL NETWORKS							
Code	Description	Connection	No. Chorus modules	Pack Carton			
GW 12 441	SUB-D 9 contacts	Weld-in	2	1/12			
GW 12 442	SUB-D 15 contacts	Weld-in	2	1/12			
GW 12 443	SUB-D 25 contacts	Weld-in	3	1/16			
GW 12 445	BNC 50/75/93 cavo RG 58/59/62	Weld-in	1	1/12			

CHARACTERISTICS: GW12445 BNC 50 Ohm (Ethernet networks); BNC 75/93 Ohm (video control systems, terminal connection).

APPLICATIONS: SUB-D connectors suitable for point-point connections for interfacing computers, peripheral devices, modems, etc.. NOTES: circuit identification label included.

120