



# CONNECTUS

Modular plastic power strip.

**The advantages at a glance**

- Very good value for money
- Exclusive to the specialist trade
- Wide range
- High-grade technology
- Tested components
- Halogen and PVC-free socket recesses

Max. 16A / 3680W



· Supply cable: 2.0 m H05VV-F 3G 1.50 mm<sup>2</sup>, black

Art. no. | Version | Dimensions: (L x W x H)

CONNECTUS		
1x rocker switch, orange		
330.100	· 4 socket outlets with earthing contact	· approx. 355 x 72 x 49 mm
330.101	· 6 socket outlets with earthing contact	· approx. 440 x 72 x mm
330.102	· 9 socket outlets with earthing contact	· approx. 570 x 72 x 49 mm
330.103	· 12 socket outlets with earthing contact	· approx. 695 x 72 x 49 mm

CONNECTUS 6x earthing contact		
1x overvoltage protection, 1x orange rocker switch		
330.104	· 6 socket outlets with earthing contact · Overvoltage protection · Visual function and fail indicator	· approx. 480 x 72 x 49 mm


CONNECTUS 6x earthing contact		
1x overvoltage protection + mains and frequency filters, 1x orange rocker switch		
330.105	· 6 socket outlets with earthing contact · Overvoltage protection + mains and frequency filters · Visual function and fail indicator	· approx. 568 x 72 x 49 mm

CONNECTUS 1 + 4x earthing contact		
Master & slave		
330.106	· 1 master + 4 slave socket outlets with earthing contact · Adjustable threshold value	· approx. 480 x 72 x 42 mm

CONNECTUS 1 + 4x earthing contact		
Master & slave, with overvoltage protection + mains and frequency filters		
330.107	· 1 master + 4 slave socket outlets with earthing contact · Adjustable threshold value · Overvoltage protection + mains and frequency filters · Visual function and fail indicator	· approx. 610 x 72 x 49 mm



Socket outlets

Max. 16 A / 3680 W  



- Supply cable: 2.0 m H05VV-F 3G 1.00 mm<sup>2</sup>, with black IEC non-heating appliance plug, red socket outlets

Art. no. | Version | Dimensions: (L x W x H)

**CONNECTUS, 3x earthing contact**

## 1x 10A fuse

330.300	<ul style="list-style-type: none"> <li>· 3 socket outlets with earthing contact, red</li> <li>· Miniature fuse, 10A</li> </ul>	· approx. 273 x 72 x 46 mm
---------	--	----------------------------

Max. 16 A / 3680 W  

- 1.5 m supply cable: H05VV-F 3G 1.50 mm<sup>2</sup>,
- Foot-operated switch with 2-pole cut-out
- Activating the foot switch halts unnecessary standby power consumption in stand-by mode by the connected devices

Art. no. | Version | Dimensions: (L x W x H)

**CONNECTUS Energy Saver**

## 1x foot-activated switch

330.142	<ul style="list-style-type: none"> <li>· LED function indicator in foot switch</li> <li>· 1.5 m H05VV-F4G 1.50 mm<sup>2</sup> cable to switch</li> <li>· 6 socket outlets with earthing contact</li> </ul>	· approx. 442 x 72 x 49 mm
---------	--	----------------------------



GREEN

**6x earth contact black/grey, child-proof, 1x foot-activated switch with LED, black**

330.153	<ul style="list-style-type: none"> <li>· H05VV-F 3G 1.50 mm<sup>2</sup> supply cable, 1.5 m, black, to plug</li> <li>· H05VV-F 4G 1.50 mm<sup>2</sup>, 1.5 m, black, to foot switch</li> <li>· 1x full equipment protection (OVP + mains and frequency filters)</li> <li>· Does not open, cannot be reconnected</li> <li>· Packaged in carton</li> </ul>	· approx. 572 x 72 x 49 mm
---------	--	----------------------------

Max. 16 A / 3680 W  

- Supply cable: 2.0 m H05VV-F 3G 1.50 mm<sup>2</sup>, black, with right angle plug with earthing contact
- External button (foot-activated switch) on 2.0m cable
- Also cuts off standby consumption from master socket

Art. no. | Version | Dimensions: (L x W x H)

**CONNECTUS**

## 1x integrated automatic switchoff device

330.140	<ul style="list-style-type: none"> <li>· 1 master + 4 slave socket outlets with earthing contact</li> <li>· With integral automatic switchoff device with external button</li> <li>· Adjustable threshold value</li> </ul>	· approx. 538 x 72 x 49 mm
---------	--	----------------------------



GREEN

Max. 16A / 3600W  · Supply cable: 2.0 m H05VV-F 3G 1.50 mm<sup>2</sup>, black

Art. no. | Version | Dimensions: (L x W x H)

CONNECTUS		
1x rocker switch, orange		
330.100F	· 4 UTE socket outlets	· approx. 355 x 72 x 49 mm
330.101F	· 6 UTE socket outlets	· approx. 440 x 72 x 49 mm

CONNECTUS 6x UTE socket outlets		
1x overvoltage protection + mains and frequency filters, 1x orange rocker switch		
330.104F	· 6 UTE socket outlets · Overvoltage protection + mains and frequency filters · Visual function and fail indicator	· approx. 480 x 72 x 49 mm

CONNECTUS 1 + 4x UTE socket outlets		
Master & slave		
330.106F	· 1 master + 4 slave socket outlets with earthing contact · Adjustable threshold value	· approx. 480 x 72 x 49 mm



### Overvoltage protection with filter

Overvoltage protection – conforms to DIN VDE 0620-1:-2002-01, EN 61643-11:08-2007, type 3, discharge current 6.5 kA, response time < 25 nS. Suitable for 16A (miniature fuse on request) with varistors, temperature fuse, gas discharge arrester, visual LED function and failure indicator (acoustic signalling also available on request).

Mains and frequency filters – conforming to VDE 0565-3:05-2006 for voltage peaks up to 30 MHz, damping diagram on data sheet.